



RW INOX



 RW INOX è una macchina di alta gamma, sostenibile e rispettosa dell'ambiente. L'acciaio inox con cui è quasi interamente costruita è infatti il materiale più riciclabile e riciclato del mondo. Questa macchina è adatta a qualsiasi impiego, non teme il tempo, è più resistente alla corrosione ed al deterioramento, rispetto a macchine costruite con altri materiali come plastica e ferro.

- Costruita interamente in acciaio inox 430 satinato
- Serbatoio gasolio integrato nella struttura, capacità 20 lt
- Caldaia verticale con camicia in acciaio inox
- Riscaldamento acqua fino a 90°C
- Motore elettrico a 4 poli 1450 rpm anodizzato
- Pompe acqua Interpump Evolution
- Aspirazione detergente in bassa pressione, optional in alta pressione con il kit vaschetta acqua
- Modelli disponibili fino a 9,5 HP
- TotalStop
- Ruote piene con mousse anti foratura
- Uso industriale






 RW INOX is a high-end, sustainable and respectful machine. The stainless steel is in fact the most recyclable and recycled material in the world. This machine is suitable for many different works, durable and much more resistant to deterioration, compared to machines done with materials such as plastic and iron.

- Are made all of 430 stainless steel
- Built-in flue tank (20 lt)
- Stainless steel vertically boiler
- Outlet max water temperature: 90°C
- Anodized 4-pole motor (1450 rpm)
- Interpump Evolution water pumps
- Low-pressure detergent suction, optional high-pressure detergent suction (only models with water tank)
- Models up to 9,5 HP
- TotalStop device
- With 4 pneumatic wheels

CODICE CODE	MODELLO MODEL	POMPA PUMP	ALIMENTAZIONE SUPPLY VOLTAGE			BAR	LT/H	KW	HP	RPM	TEMP. °C	DIESEL LT	KG	LXPXH CM
			Ph	V	Hz									
000216	RW INOX 160/15	Interpump serie 58 EV	3	400	50	160	900	4	5,5	1450	90°	20	120	71 x 112 x 90
000223	RW INOX 160.21	Interpump serie 59 EV	3	400	50	160	1260	5,5	7,5	1450	90°	20	130	71 x 112 x 90
000006	RW INOX 200.15	Interpump serie 58 EV	3	400	50	200	900	5,5	7,5	1450	90°	20	130	71 x 112 x 90
000227	RW INOX 250.15	Interpump serie 59 EV	3	400	50	250	900	7	9,5	1450	90°	20	140	71 x 112 x 90
000015	RW INOX 200.21	Interpump serie 47	3	400	50	200	1260	7	9,5	1450	90°	20	140	71 x 112 x 90

RW INOX

DOTAZIONE STANDARD STANDARD ACCESSORIES

MODELLO MODEL	CODICE CODE	DESCRIZIONE DESCRIPTION	DETTAGLI DETAILS	
Tutti All	4012305003	Pistola con Swivel max 310bar max 30lt/min Gun with Swivel (max 310bar max 30lt/min)	max 310bar max 30ltmin	
Tutti All	390124	Spezzone lancia angolata senza ugello Bent lance without nozzle	1200 mm max 310bar max 40lt/min	
Solo senza vaschetta acqua Without water tank	4050502000	Testina detergente regolabile Adjustable Detergent head	Max 250 Bar 30 lt/min	
Tutti All	000270	Kit tubo gomma mandata 10 m 10 m rubber delivery hose kit	R2 5/16" FD-FD 3/8 + Man Max 400 Bar	
160/15 250/15	000274	Ugello con getto a lama 25° attacco 1/4" MEG Fan shape nozzle 25°, 1/4" MEG connection	04	
200/15	000275		045	
160/21 200/21	000277		06	

EQUIPAGGIAMENTO OPTIONAL OPTIONAL EQUIPMENT

CODICE CODE	DESCRIZIONE DESCRIPTION	
000252	Maggiorazione per kit vaschetta acqua con aspirazione detergente in alta pressione Increase for water tank kit with detergent adjusting suction in high pressure	
000257	Kit avvolgitubo manuale inox (staffa+tubo di raccordo+avvolgitubo) senza tubo S.Steel Manual hose reel kit (brackets+joint hose+manual hose reel) without hose	

HYDRO S.R.L.

Via dell'Artigianato 3 29015 Castel San Giovanni – PC (Italy)

Tel. Ufficio + 39 0523 340826 Cell. Ufficio + 39 339 5392747