

Zeta



IDROPULTRICE AD ACQUA CALDA PER USO SEMI-PROFESSIONALE, LA PIÙ PICCOLA DELLA GAMMA

- Pompa sistema bielle/ manovella
- Valvola di regolazione e by-pass incorporata
- Robusto telaio in lamiera verniciata
- Caldaia orizzontale con ottime prestazioni e serpentina a doppia spirale
- Flussostato controllo bruciatore
- Scatola elettrica di comando con protezione ip55
- Motore elettrico con termico incorporato raffreddato da convogliatore in alluminio
- Serbatoio gasolio da lt 5
- Economicità d'uso (alto rendimento energetico della caldaia e basso consumo elettrico)
- Sicurezza e rispetto dell'ambiente (ridotta emissione di incombusti, contenuta rumorosità di funzionamento)
- Versatilità di impiego (termostato per regolazione temperatura fino a 85°, valvola di regolazione pressione, variazione portata, aspirazione detergente in bassa pressione)
- Facilmente accessibile in tutti i suoi componenti, per regolazioni e manutenzione
- Ridotte dimensioni

HOT WATER HIGH PRESSURE CLEANERS

- Pump with 3 ceramic pistons, eccentric shaft system connecting rods
- Regulating valve with built-in bypass • strong frame in sheet metal painted with epoxy powders
- High efficiency boiler, with quality steel coil, integrated burner • burner control flow meter
- Electric control box with ip55 protection
- 5 lt diesel tank
- iElectric motor with built-in thermal relay, forced cooling with double acting conveyer in aluminium
- Hose, lance with automatic gun as standard professional accessories
- Energy efficiency (high efficiency of the boiler and low electricity consumption)
- Safety and protection of the environment (very low emissions of unburned substances and low operating noise level)
- Versatile use (adjustments allowed: temperature until 85°, pressure, flow rate, detergent use..)
- Easy maintenance for any component
- Small dimensions



Motopompa professionale 2800 giri a tre pistoni in ceramica con sistema ad albero eccentrico e bielle con portata da 450 a 510 lt/h.

2800 r.p.m. professional motorpump (rod/crank system), with 3 ceramic pistons. Flow rate from 450 to 510 lt./h.

Modello Model	Codice Code	Pressione (Bar) Pressure (Bar)		Portata Flow Rate		Vtaggio Voltage	Potenza Power		T Max °C	Peso Weight	Dimensioni Dimensions
		NOM	MAX	L/MIN	L/H		KW	HP			
ZETA 100.8	20.07.00100	100	105	8,5	510	230/50/2850	1,6	2,2	85	63	60X40X75
ZETA 120.7	20.07.00600	120	125	7,5	450	230/50/2850	1,6	2,2	85	63	60X40X75
ZETA 120/7 STEAM	20.07.10600	120	125	7,5	450	230/50/2850	1,6	2,2	150	63	60X40X75

DOTAZIONE STANDARD / STANDARD EQUIPMENT



**1 TUBO PROFESSIONALE R1 DA MT 10
+ INNESTI RAPIDI**
1 R1 10 MT HOSE + INLET/OUTLET
COUPLINGS



**1 PISTOLA CON MANICO
+ PROLUNGA LANCIA (60CM)**
1 GUN WITH HANDLE
+ LANCE EXTENSION (60CM)



**1 UGELLO-LANCIA
1 HP NOZZLE**

ACCESSORI A RICHIESTA / OPTIONAL ACCESSORIES



0K.07.03200

**KIT SPAZZOLA ROTANTE
ROTATING BRUSH**



0K.07.03900

**KIT LANCIA SCHIUMA
SEMIPROFESSIONALE
SEMI PROFESSIONAL
FOAM LANCE**



0K.07.03700

**KIT UGELLO ROTANTE
PROFESSIONALE (+PROLUNGA)
ROTATING PROF. NOZZLE
(+EXTENSION CM 70)**



60.00.48900

10 mt

60.00.49000

15 mt

60.00.49100

20 mt

**KIT STURATUBI
PIPE CLEANING KIT**



60.90.01800

11-15 lt

60.90.01801

15-18 lt

60.90.01802

18-21 lt

**KIT SABBIANTE
PROFESSIONALE (TUBO E SONDA)
PROFESSIONAL SAND KIT**